




SECTION 2 (201 TO 299)
TYPE CRR-20104 RECTIFIER POWER SUPPLY

CAPACITORS

C-201	HV Filter	4.0 Mfd, +10% -3%, 600VDCW, Oil-paper.
C-202	HV Filter	Same as C-201
C-203	HV Filter	Same as C-201
C-204A	Primary Bypass	0.1 x 0.1 Mfd, +10% -3%, 400V
C-204B	Primary Bypass	DCW, Oil-paper

FUSES

F-201	Primary Line	1.0 Amp. 250V, 3AG
F-202	Primary Line	Same as F-201
F-203	Secondary Ground	1/8 Amp. 500V, 3AG

RECEPTACLES

J-201	AC Input	3-contact, Shielded
J-202	Power Output	5-contact, Shielded

REACTOR

L-201	Filter Choke	30 H, 0.025 Amps, 870 ohms
-------	--------------	----------------------------

METER

M-201	Compensator Volts Indicator	0-150 V, AC, Bakelite
-------	--------------------------------	-----------------------

RESISTORS

R-201	HV Bleeder	25,000 ohms, +-5%, Style C, 15W, WW
R-202	HV Bleeder	Same as R-201

SWITCHES

S-201A	Power On-Off	DPST, Toggle, Bakelite Case,
S-201B	Power On-Off	3A-225
S-202	Compensation 1	SPDT, Toggle, Bakelite Case,
		3A-125V
S-203	Compensation 2	Same as S-202

TRANSFORMER

T-101	Power Transformer	60 Cycles, AC; 510/255 volts, 0.025 Amp; 12.6V, 0.9 Amp; 6.3V, 0.5 Amp.
-------	-------------------	---

VACUUM TUBE

V-201	Full Wave Rectifier	Type 84
X-201	V-201 Socket	5-contact, Ceramic

PLUGS

P-301	Power Cable, Supply End	5-contact, 1-1/4" OD, Shielded, Straight
P-302	Power Cable, Indicator End	5-contact, 1-1/4" OD, Shielded, 90-degree, 8-position
P-303	AC Line Cable, Rectifier End	3-contact, Shielded

CABLING

W-301	Power Cable	5-cond; Shielded rubber covered; 0.495", 72" long
W-302	AC Line Cable	3-cond; Shielded rubber covered; 95" long