

EAC 4996

RF Subchassis

J208 Pin	Ω to Gnd	Reading
A	92K	106.8K
B	0.8	3.5
C	Inf	Inf
D	Inf	Inf
E	Inf	1650 K
F	100	9
H	0	1.5
J	Inf	Inf
K	Inf	Inf

Crystal Oscillator Subchassis

J410 Pin	Ω to Gnd	Reading
A	Inf	Inf
B	10	11.2
C	Inf	Inf
D	0	3.8
E	11	15
F	11	15
H	0	1.1

VFO Subchassis

J709 Pin	Ω to Gnd	Reading
A	Inf	Inf
B	Inf	Inf
C	Inf	Inf
D	Inf	Inf
E	Inf	Inf
F	0	1.5
H	3.5	4.3
J	Inf	Inf
K	Inf	Inf

IF Subchassis

J512 Pin	Ω to Gnd	Reading
1	Inf	Inf
2	50K	61.3K
3	54K	51.7K
4	500K	474K
5	Inf	Inf
6	Inf	Inf
7	Inf	Inf
8	Inf	Inf
9	Inf	Inf
10	440K	460K
11	Inf	Inf
12	27	30
13	Inf	Inf
14	0 to 20	7.3
15	132K	144K
16	100K	112.8K
17	0	2.6
18	0	2.6
19	Inf	Inf
20	0.5	2.7

Power Supply Chassis

J811 Pin	Ω to Gnd	Reading
1	< 0.1	1
2	0	1.5
3	Inf	Inf
4	Inf	Inf
5	Inf	Inf
6	Inf	Inf
7	Inf	Inf
8	Inf	Inf
9	Inf	Inf
10	< 0.1	4.6
11	0	4.6

AF Subchassis

J619 Pin	Ω to Gnd	Reading
1	3.6	75
2	90K	88.3K
3	90K	91.4K
4	90K	92.2K
5	90K	88.8K
6	Inf	Inf
7	Inf	Inf
8	Inf	Inf
9	58	154.2
10	< 0.1	4.1
11	0	3.1

J620 Pin	Ω to Gnd	Reading
1	Inf	Inf
2	940K	927K
3	Inf	Inf
4	470K	455K
5	200	59
6	Inf	Inf
7	Inf	90K
8	Inf	Inf
9	Inf	Inf
10	Inf	Inf
11	Inf	Inf
12	Inf	Inf
13	0	11.5
14	1.36M	1.35M
15	Inf	Inf